


I'm not robot  reCAPTCHA

Continue

Honda generator 3000 manual



Honda generator 3000 wont start. Honda 3000 generator shop manual. Honda ex 3000 generator manual. Honda 3000 generator repair manual. Honda 3000 generator parts manual. Honda em3000 generator manual. Honda eg 3000 generator manual.

In this position, the exhaust and suction valves are heavy and will help protect the engine from corrosion. Starter grip 25 Page 309. To avoid extended heating periods, keep the switch off until the engine reaches operating temperature. L11 Page 16ac Applications 1 . The AC power switch is off and nothing is connected to the DC terminals? C. All information in this publication is based on the latest product information available at the time of approval for printing, Honda Motor Co., Ltd. The use of parts of the quality requirement which is not of quality equivalent may damage the Generator. 15 Page 20 MANUFACTURERS SERVICES MESSINSPECTION6 GESTION1 CleanerElementFuel FilterCleaning0000 (1) Cleaning Spark Plug Maintenance Valve Clearance00 (2) Replacement Chamber Valve Clearance00 (2) Fuel line inspection (replacement if necessary) Spark Arrestor Note (1). Service plus frequently every 100 ARTINGING ACCESSIVELY USED IN DUSTY AREAS . (2); these items should be repaired by an authorithowner has the appropriate tools and A' the mechanically shop. 16hours.honda dealer manual, unless it is not possible. Headquarters the Honda 21Tool Kit the tools provided are necessary for performing simple fixes and repairs. Change the oil drain to the oil while the A' st engine is hot to ensure fast and complete Raining. 1. Remove the exhaust plug and the filter cap and discharge the oil. Scroll the clips, remove the air filter cover, and remove the element. element Page 232. Almost all problems are resolved in this way. When The switch A' aimed at Ae 4Y1180V only ... Location, A' only 120v AC can be used. If OK, try starting the engine according to the instructions. Use of generator 6. If there are no Replace the plug. Turn on the engine. Is there enough oil in the crankcase? 5. Clean any form of dirt around the candle base, then remove the The plug. Is the AC switch on? 2. Remove the filter cup. 2. Clean the cup thoroughly. 3. Get thoroughly. 3. Get thoroughly. Is there a spark at the candle (page 27)? Switch off the fuel valve. FUEL 14 VALVE Page 197. HANGER I / J) SPARK SPARK COVER FUEL TANK CAP 31 Page 5 10. TRANSPORT/DOWN 9. If the engine does not start yet, take the generator to the dealer. Push the throttle rod into OPENING while the engine warms up. CHOKER OD7. Coat hanger KIT INSTALLATION Coat hanger 6 mm BOLT I WARNING: Make sure to set the coat hanger to the position indicated below. Non-cleaning or vegetable oils are not recommended. And use Honda 4 stroke oil, or an equivalent high detergent, premium quality engine oil certified to meet or exceed the requirements of the U.S. automaker for service classification SE or SF. The 7th. Pull the throttle to CLOSE CHOKER OD VALVE Page 133* Make sure the automatic heater turns on AUTO THROTTLE SWITCH. Switch is off, otherwise you will need more time for -4. The exhaust contains poisonous carbon monoxide gases. WARNING-Use only original HONDA parts or equivalent. GENERATORS SAFETY To ensure safe operation. Place the generator at least 1 m (3 ft) away from buildings or other equipment while the generator is running. Operate the generator on a flat surface. If the generator is tilted, a fuel leak may occur. The exhaust gases contain poisonous carbon monoxide. Never operate the generator in a fence. Make sure you provide adequate ventilation. Know how to quickly stop the generator and understand how all controls work. Is the fuel valve above? 3. GENERATOR SAFETY .. If you encounter a problem that the dealer does not resolve satisfactorily, please discuss it with the dealer's management. Throw it away if insulator cracked or chipped. 6. Measure gap with a sensor. Space should be 0.6-0.7 mm (0.024-0.028 inches). 3. No electricity to AC receptacles: 1. Gasoline is reaching the You can write: American Honda Motor Co., Inc. Minor overload will not change the circuit breaker and will reduce the service life of the Generator. 12 Page 176. Specifications Dimensions SEB3000: 605 x 425 x 620 mm (23.8 x 16.7 x 24.4 in) EB4000: 650 x 425 x 650 mm (25.6 x 16.7 x 25.6 in) EB3000: 64.5 kVA (142.2 lb), EB4000: 81.5 kVA (179.7 lb) length x width x height 3 weights honda g e300 model engine type displacement [drilling x stroke] compression ratio manual filling speed system ignition saturation fuel Tank Capac Spark Plug Honda G E4004 Strary, side valve, 1 cylinder 272 cm3 (16.6 cu in) 1406 cm3 (24.8 cu in) [86x70mm (3.4x2.8 inches)] [76x60mm (3.0x2.4 inches)] [6.8: 16.5: 13.600 Rpm forced Air Cooling in flywheel magneto 1.21.2 litre Q (5.1 (1.3USQT) QT) 16.5 Q (4.4 US GAL) BR4HS (NGK) W14FSPR-U (ND) Generator Voltated Frency Rated Am Generator per Eac Output Ropitued Output Maximum Exumnt 120 V1240 V60 HZEB3000: 23.5 / L 2AEB4000: 32 / 16 EB3000: 2.8 KVA (2800 EB4000: 3.8 KVA (3800 EB3000: 3.0 KVA (3000 EB4000: 4.0 KVA (4000 W) W) 29 Page 34 GLNTRATOR Control box KM CONTROL VALVE ZV / ZUUV-1IT-120V ---- FOOD WH, TELOST WLK Blackgreened EGR Greenground terminal Page 35 12.6 mm Bolt Caution: Hanger Kit Installation Hanger Make sure to set the hook to the position as illustrated below. Hanger / Spark Plug Cover Fuel Tank Cap 31 Page 36 Current Customer Service Contact Information: United States, Puerto Rico and U.S. Virgin Islands: The staff of the Honda Electrical Equipment Dealer is professionally trained. Page 7 9. Troubleshooting A. Specifications L. Wiring diagram 12. Remove the cover of the candle. 2. Clean dirt close to the base of the candle. 3. Remove the cover of the candle. Cap Spark Plug Cover Plug Cap 27 Page 264. Avoid getting dirt, dust, petrol substitutes are not notorous to the power supply system Bigasoline is extremely flammable and explosive under certain conditions. E fuel in a well ventilated area with the engine stopped. Do not smoke or allow flames or sparks in the area where the generator is refuelled or where the gasoline is stored. Do not overfill the tank and make sure the filling cap is refuelling safely by refuelling. Be careful not to spill the fuel while refuelling the refuelling. Turn the engine switch on. engine switch / 9 Page 145. STOPPING LING ENGINE TO Stop the engine in case of emergency, turn off the engine switch Off. in Normal use: 1. They should be able to answer any questions you may have. Black G Page 4 Contents Contents 1. Page 62. Fuel vapour or spilled fuel can ignite. At - position 120v / 240v 2. you can use sources at both 120v and 240V. 2. Switch on the AC circuit breakers. 3. Connect the appliance. Note: This generator is equipped with equipment for stable voltage supply. AVR AVR (Automatic voltage) Caution: Make sure that appliances do not exceed the rated load for 30 minutes and never exceed the maximum load. Maintenance program and regulation Generator in the best operating condition. inspect or Service as scheduled in the table on the next page. To keep their engine from the engine before performing any maintenance. Fuel vapour or spilled fuel May ignite. Drains Crew 4. Almost all problems solved this way. If you are dissatisfied with the decision made by dealer management, contact the Honda Electrical Equipment Relations Office. The service manager or the General Manager can help. 8. Is the engine ignition activated? Check the fuel level. Using petrol with a research octane of 91 or greater or a pomp octane of 86 or greater. Do not use a tank of oil/gasoline water in the fuel tank. A dirty gasoline, corrected as needed by turning on the side electrode. 7. Attach the washer plug. Installation of the hook kit 12 481 113 162 426 293 031 Page 51 ... 51 ... id thsoped id azeserpl al eracrifrev rep attimram alled ociracs id arutrepal' erallortnoC. ociracs id obtut li erevounir rep mm 3 ad inollub eid erattimra. attimram al erevounir e idad i e inollub i erattimra. 4.3.2. 1. arzeiciffe'l enretntam rep ero 001 ingo enozinetnam a otspotos eresse eved otsera id ovitisspsid li ENOIZNETTA. adiac otlom Aras attimram al erevecorp id amirp eraderfar id olettinesoc. enoizunf ni otas' A' erotareng li eSwxpcnemnam retserra krapS72 eqaP 1. - IN22HCNERW GULPni820.0-420.0(mm)7.0-6.0PAGGULPulg thgtl1.oirporpmi erotac id alovretni nu noc allitnics anu ierasu IAm GULP. erotareng li eraiggnedd etnemlibaborp e odlac otlom erarnevid A'up etnemairporpmi nU avisssecus anigaP 14/1 etnedecerp anigaP ni tuo mooZ avisssecus anigaP 14/1 etnedecerp anigaP tuo mooZ 21 anigaP 33 OMEM avisssecus anigaP 14/1 etnedecerp anigaP ni mooZ 11 anigaP amelborp led ataligatted enoizircsed anU eAAeA onofelet id oremun e ozziridni. emon ortsov li eAAeA otaiuca'd atad eAAeA ohccerappa ortsov li evres ehc erotidnevrl led ozziridni e emoN eAAeA adnoH ohccerappa'l otudnev ah iv ehc erotidnevrl led emoN eAAeA eires id e olleddom id oreman eAAeA :inoizamrofini itneuges el icseinof ,imaich e ivircv odnauQ TSE 00:91 - 03:8. F-M 0046-794 J077(onofelet O 7488-50003 AG. atterahplA evirD inocrM 0094 eciffo snoitaleR remotsuC noisivid tneipiugE rewof. 421 eqaP 7SREKAHRBTUUCRIC.otagelloC A' ocirac nu es eraivva ad eliciffid eresse ebbertop erotareng li itneps onais AC itrottrretni ilq ehc isarucissa A. aenatnemom enoizatzemila olos onodeihr ehc vitisspsid noc ozzilitt' rep ecaciffa A' non ohccerappa'Ll. ereppma 1 a irotrefni icirttele icirca e ednopsir non attenamotua'Ll. etnarubracc id omusnoc li ominim la erurdir rep otaligisnoc A' OTUA:ATON. anoizunf non attenamotua'l .otavitissid A' odnauQ. anips alled oppat len aleddnac al erallatsni .ittefid ilautnevs EB2acirttele arutaihccerappa'l o arutaihccerappa'l erallortnoC clean up if necessary. Remove the spark stop device from the muffler. Clean the screen and inspect it for damage. Manually thread the plug to avoid threading. 8. Tighten a new candle 1/2 round with the wrench to compress compress compress erotom 2.5 R NEERG . d e HCTIWS EBOTOM PHRG RETRATS YATS A GNIDNUORG. B23 eqaP 72. oiranossecnoc lad erotareng li eratrov ,aivva is non erotom li eS. 8. inoizurtsi el odnesoc erotom li eraivva da erarovp . K0 eS. anips al eruttissoc ,elittinics onos ic non eS. otellrig . otovu lus onatlas ellitnics es eredev rep olucnir id otmeiaivvaal erart. ,elaretal erortl arret A. d erotom led erotturretniad eredneccA. c.alednac alled okcuppac len aleddnac al erallatsni . b.alednac al erevounir idniug, alednac alled esab alla onotoni ocrops of eritUP ?etnarubracc aznatsabba A'ac. 1. aivva is non erotom li odnauQ ?retrac len oilo aznatsabba A'ac .etnemataidemi amref is am aivva is erotom li odnauQ .ittefid ilautnevr rep acirttele arutaihccerappaal o ohccerappaal erallortnoC .otnemaiivaal opod .Arengeps is erotom led erotturretniad. oiartnroc oscac ni . a13 eqaP CD alla ednesoc62772 anigaP allednac alla allitnics anu A'ac. erotom li eraivva o aleddnac al erasetid amirp attuicsa ais aeraal ehc isarucissa . etnarubracc id aticisurof id oscac ni 1-h. 1. deppagetnematterroc eresse eved aleddnac al. itisoped id ovirp e erotom led otmenaoizunf otterroc li eritnarag rep JDN(U-RSF41W)KGN(SH4RB . atadnamoccar aleddnac allednac ozivres52 eqaP EVLAVLEUF. erotom li eraivva id amirp attuicsa ais anoz al ehc isarucissa e etnarubracc id etidrep ilautnevs eracrifrev ,ortlif appoc al otallatsni reva opoDm. teksag li eraiggnedd noN .etnarubracc led alovlab al noc ociracs id etiv al erattimra. ,erallortnoc rep .d92 eqaP PUC42RET; A' eAIF. orucis odom ni erarres e ortlif led appoc al eruttissoc .c.ottada erotinetnoc ni n etnarubracc led ototabres len anizab al eracracs e etnarubracc led alovlab al eredneccA . b.ortlif led appoc al erotavus e erevounir .atneps etnarubracc led alovlab al noC . 6 .etnemadlas atarres eresse eved aleddnac al:ENOIZNETTA. lides i opod orig id 4/1-8/1 olos eredeicir ebbervod ,anips anu odnazzilittuir ats is eAlednor odnauq odnauq a onif otneivaiva id arutangupmiad erart' eVERCSNIARD. otada erotinetnoc nu ni anizab al eralocS .oiravid li orevaritla eratlus ellitnics es eredev rep olucnir erotaiivaal erart. ,onroiggos la elaretal odortteleal arret A. 0133 anigaP It is heard; The piston is coming to a stroke of proposing. Is gasoline reaching the carburetor? To control, loosen the exhaust screw with the fuel valve ON. H-1SE The fuel is poured, make sure the area is dry before testing the spark plug or start the engine. If the engine has not been performed for a long time, the generator should be clean. 1. Switch off the fuel valve. A fire or an explosion may result. CAUTION: Never perform the generator without garments. The AIR THE AIR CLEANER. If fuel is poured, make sure the area is dry before starting the engine. Fuel Tank Cap Page 113. When the engine starts but stops immediately: is there enough oil in the crankcase? Otherwise, the motor switch turns off after starting. No electricity to AC containers: 1. Transport / storage and Transport of the generator, turn off the And/keep engine The generator level to prevent fuel spill. If the TEARGE must be performed, make sure the area is well ventilated. C. Starting the engine. You can write: American Honda Motor Co., Inc. Power Equipment Division Customer Relations Office 4900 Marconi Drive Thareta, GA 30005-88470R Phone: (770) 497-6400 MF. 8:30 - 7:00 pm Esthend Provide the following information: A e A. A e model and serial numbers - name of the retailer who sold the Honda electric equipment to you - name and address of the retailer who serves your equipment - date of purchase e a - a e Name, address, and number of Telephone - Detailed description of the problem Page 3732 Page 38Memo33 Page 39ME32 Page 3 Page 2 Zoom Page 2 Page 41 Page 2 Zoom Back Zoom on the previous page 1/41 Next page MEMO 34 Page 3 Zoom Back Zoom on the previous page 1/41 Next page 32 Page 4 12 . Drain the carburetor by loosening the exhaust screw. The switch AC ' off and nothing 0. They should be able to answer any questions you may have. Engine starting 5. Turn the fuel valve on. fuel. 2. Servicemore frequently when. when. elanosrep onnad id atidrep o elanosrep onnad ivary id :sdrow. atuges non Atilbissop anu acidni :ATON INOIZURTSI :INOIZURTSI. OSIGES NON INOIZURTSI ES ATLANGES ID ATILBISSOP ANU ETACITNADN'LLAD ETNEDECERP ENOIZNETTA ELAICEPS ENOIZNETTA YAP. otudnev odnauq erotareng li noc niamerdnA

